LANDA®

Industrial Pressure Washers ...Built Right to Do the Job Right

Since 1969

head provides

■ Multi-Stage Filtering System

includes a 40 gallon holding tank with

a 500 micron mesh/100 micron duo-

polyester Pre-Filter Sock, a 50 micron Pleated Polyester Filter (20 micron on LX and DX models), a 20 micron Pleated Polyester Filter (5 micron on LX and DX models), and an Oil Absorbent Media Bag. Clean water is directed to selected tanks for reuse. or can be dumped directly to drain. pending local EPA requirements.

ECOS

Environmentally Friendly Mobile Wash and Reclaim System

- Patented Trans-Heat ■ Vacuum / Water Reclaim System with 50 feet of 2-inch vacuum hose Technology* captures exhaust from the engine to preheat water, and draggable, non-tipping suction increasing water temperatures continuous suction up to 15°F and providing better of wash water. fuel efficiency.
 - Landa Duracoil with stainless steel top wrap and 5-year warranty heats water using high-
- Conveniently placed Locked Control Panel includes key start, choke. Burner On/Off Switch. Adjustable Thermostat, and an Hour Meter with low oil indicator. Also includes reclaim pump. vacuum motor switches and Low Point Drain for water tanks.

- 4.7 GPM at 3500 PSI
- Carries up to 400 gallons
- Captures, filters and recycles wash water for continuous use
- Patented Trans-Heat Technology* provides better fuel efficiency
- Four **Polyethylene Water Tanks** provide 400 gallons of clean water and are linked for even distribution. Main Control Valve System includes easy to use valves for controlling water distribution. Feed Pump with pressure-sensing switch alleviates wear and tear on main pump.



- Honda GX660 Engine and Landa LT Pump with 7-year warranty provide 4.7 GPM at 3500 PSI of cleaning power.
- Heavy-Duty 4,000 Watt Generator produces reliable 120V AC power to the burner and vacuum.
- Durable **Swing-Away Tongue** (rated for 7.500 lbs) connects with either a 2 5/16-inch Ball Coupler or Lunette Ring (DX model), 7-pin Electrical Trailer Plug and heavy-duty 2,000 lb. capacity Swivel Jack, allowing trailer to be stored in a smaller area.



Galley storage compartment underneath the floor allows for easy storage of the vacuum hose. Shown with garden

- Two Hose Reels hold up to 100 ft. of high-pressure hose and 75 ft. of low-pressure hose.
- 30 in. x 7 ft. **Galley** allows for storage of pressure washer equipment with a removable rear gate.
- Insulated, spring-loaded Trigger Gun and insulated, dual-lance Variable Pressure Wand make it easy to switch between detergent wash and rinse modes.
- Locked compartment includes **Dual Fuel Tanks** for gasoline engine (17 gallons) and diesel burner (17 gallons). Also includes space for two detergent buckets.

9001

- Safety Features including redundant devices such as a Rupture Disk, and hightemperature shutdown to guard against excessive pressure or heat.
- Four 15-inch Black-Rim Wheels with 205/75/R15D tires on **Tandem Axles** rated at 3,500 lbs each (7,000 lbs total) with Electric Brakes on both axles and battery operated Breakaway Kit for added safety.
- Four Color-Coded Quick-Couple Nozzles made of hardened stainless steel are mounted near hose reel for ready access.

www.landa.com